



Albany UltraBig

Big on productivity and savings

www.albanydoors.us

TOUGH PERFORMANCE

From forklifts to heavy equipment, the Albany UltraBig high-speed rubber door handles openings as large as 50' x 35' with speed and reliability in the harshest environments.

Forgiveness in an unforgiving environment

The Albany UltraBig helps to avoid unplanned downtime, putting you in control of the uncontrollable with features including:

- Heavy-duty steel frame – withstands accidental impact, and rigorous environments
- UltraStrong curtain – protects against temperature extremes from -40° F and 80° F to 176° F; chemical and corrosion resistant
- Gussets and Windlok design – door functions in winds of up to 20 psf (88 mph); near airtight seal

Protect workers and enhance productivity

The Albany UltraBig helps reduce lost-time accidents and is easy to learn and operate.

- Electric bottom edge – slight contact automatically reverses the door to the open position
- Inline through-beam photo eye – detects objects in the door way and safely reverses the door before contact

Increase efficiency, lower cost

From installation to operation and maintenance, the Albany UltraBig delivers efficiency. Opening speeds of up to 12" per second eliminate compromise between speed and effectiveness.

- Counterbalanced design – fast, smooth operation; springs increase the life of the drive unit
- Structural steel frame – lasts longer; installs faster and easier
- Heavy-duty – engineered to cycle hundreds of thousands of times in rigorous environments.



Technical information

Opening speeds

Counterbalanced system Opening up to 12 in/sec (size dependent)

Door dimensions

Max height	35 ft (10,668 mm)
Max width	50 ft (15,240 mm)
Min height	30 ft 1 in (9,169 mm)
Min width	30 ft 1 in (9,169 mm)

Safety features

Photo eye	Standard
Bottom beam	Failsafe auto stop and reverse self-monitoring safety edge

Door panel

SBR	2 layers of Styrene Butadiene Rubber (SBR) with polyester cord center MSHA curtain material.
	Breaking strength 1100 lbs/in/ply
EPDM	Optional

Wind resistance

Continuous windlock Up to 20 psf (128 mph)

Door components

Counterbalanced systems	50k cycle torsion springs
Side frames	Heavy-duty steel painted Optional - Corrosion and chemical resistant coating
Idler	6" diameter, 1/4" wall thickness
Door roll	12" diameter, 0.188mm thick tube complying with ASTM A513
Bottom bar	Steel construction
Manual egress	Chain hoist
Hood	Optional
Windows	Optional - 10" x 18"

Control and drive system

Input voltage	208-240 V, 440-480 V, 575-600 V,
Motor	Up to 3.7 kW, 3 phase, 60 Hz, 20 amps
Limits adjustment	From Drive
Protection	NEMA 4/12, IP-56

We offer various options and actuation devices for all high-performance door products




Photo eye

Inline through beam photo eye keeps people and equipment safe from door contact.



Heavy-duty side frames

Heavy-duty side frames and Windlok guide system resist high wind pressures.



UltraStrong curtain



Programmable Logic Controller (PLC)

PLC Controller is customizable and easy to use (inside building).



Gussets, Windlok and Guide system

Door will resist wind loads of up to 20 psf (128 mph). Windlok & Guide system offers a near airtight seal.



Counterbalance system



Entrematic offers a comprehensive range of products for industrial, commercial, institutional and residential applications, including sectional doors, loading dock equipment, high-performance doors, residential garage doors, pedestrian door automation and openers. Built on nearly 200 years of accumulated expertise, Entrematic is the preferred partner of distributors and the number one choice of end user customers, providing innovative products, technical expertise and a portfolio of industry-leading brands including Amarr, Kelley, Serco, Dynaco, Ditec and Albany. Entrematic, Amarr, Kelly, Serco, Normstahl, Dynaco, Ditec, Albany and EM, as words and logotypes, are examples of trademarks owned by Entrematic Group AB or companies within the Entrematic Group.

The Albany products are protected by worldwide registered patents. As part of its policy of continuous product development, Entrematic reserves the right to change the characteristics of its products or components without prior notice. Disclaimers: For a correct use of our products, please refer to our manual. Everything that is mentioned in this brochure is only valid under the terms of use in the user manual and on condition that the door was properly installed and maintained and has not undergone abuse nor neglect.

© Entrematic Group AB, 2018 Technical data subject to change without notice.

Albany Doors
Tel: 1-800-252-2691
info.us.albany@entrematic.com
albanydoors.us • albanydoors.ca

ENTRE/MATIC

